

## RU-850LTH/5

Order No. 0259560

### Dynamic hand-held UHF PLL microphone transmitter

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Adjustable sensitivity ( $\pm 15$  dB)
- Lock function/mute function
- 5-level display for indicating battery status and low battery alert, backlit LCD

Model	RU-850LTH/5
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	30 h
Audio frequency range	50-16,000 Hz
Max. sound pressure	148 dB
Dimensions	$\varnothing 51$ mm x 269 mm
Weight	242 g

- Switchable transmitting power



## RU-850LTB/5

Order No. 0259360

### UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 comp. preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Selectable sensitivity ( $\pm 15$  dB); additional 20 dB attenuation can be activated as required

Model	RU-850LTB/5
Description	pocket transmitter
Carrier frequency range	506-542 MHz
Audio frequency range	50-16,000 Hz
Operating time	30 h
Transmitting power	10/50 mW
Power supply transmitter	2 x batt. AA size, alkaline (not supplied)
Dimensions transmitter	62 x 97 x 20 mm
Weight transmitter	76 g
Connections transmitter	4-pole mini XLR

- Lock/mute function
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power



## RU-850TH/5

Order No. 0259851

### Dynamic hand-held UHF PLL microphone transmitter

- Bandwidth: 36 MHz
- 6 groups, each with 22 compatible preset channels (114 channels)
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Sensitivity adjustment ( $\pm 15$  dB) and transmitting power (10/50 mW) can be configured via receiver
- Mute function, low battery alert
- Special design to reduce handling noise, structure-borne noise and acoustic feedback

Model	RU-850TH/5
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	30 h
Audio frequency range	60-15,000 Hz
Max. sound pressure	148 dB
Dimensions	$\varnothing 51$ mm x 269 mm
Weight	235 g



## RU-850TB/5

Order No. 0259849

### UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- 6 groups, each with up to 22 compatible preset channels (114 channels)
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Sensitivity ( $\pm 15$  dB), additional 20 dB attenuation and transmitting power (10/50 mW) can be configured via receiver

Model	RU-850TB/5
Description	pocket transmitter
Carrier frequency range	506-542 MHz
Audio frequency range	60-15,000 Hz
Operating time	30 h
Transmitting power	10/50 mW
Power supply transmitter	2 x batt. AA size, alkaline (not supplied)
Dimensions transmitter	62 x 97 x 20 mm
Weight transmitter	69 g
Connections transmitter	4-pole mini XLR

- Bandwidth: 36 MHz
- Mute function
- Low battery alert



**There are restrictions or requirements in the EU!**

**Please read the notes on wireless systems in the section "IMPORTANT INFORMATION"!**