

BH-010USB

Order No. 1000175



Professional stereo headphones with electret boom microphone

- For operating directly at a PC or laptop
- No driver installation required, device will be identified automatically
- Closed system
- Excellent sound characteristics, very comfortable to wear
- Flexible microphone boom, folding, continuously adjustable
- Padded ear cushions
- 2 m cable with single-sided cable inlet, volume control at the cable and USB port

Model	BH-010USB
Headphone driver	Ø 30 mm
Type of transducer	dynamic
Max. input power	100 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	105 dB/mW
Transmission range, mic.	50-15,000 Hz
Microphone system	electret, omnidirectional
Microphone sensitivity	13 mV/Pa
Power supply	= 5 V via USB interface
Cable	2 m, single-sided cable inlet
Plug	1 x USB Type-A
Weight w/o cable	61 g



HPM-535

Order No. 0220210

Professional stereo headphones with electret boom microphone

- Excellent sound characteristics, comfortable to wear
- Semi-open system, over-ear
- Compatible with sound cards
- Ideally suited for gaming
- Adjustable microphone boom
- Padded ear cushions and headband
- 2 m cable with single-sided cable inlet and 3.5 mm plugs

Model	HPM-535
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	1,000 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	64 Ω
Headphone sensitivity	104 dB/mW
Transmission range, mic.	100-15,000 Hz
Nominal impedance, microphone	680 Ω
Microphone system	electret
Microphone sensitivity	6.3 mV/Pa/1 kHz
Power supply	= 1.5-10 V
Cable	2 m, single-sided cable inlet
Plug	2 x 3.5 mm plug, gold-plated
Weight w/o cable	308 g



HP-565

Order No. 0221300

Professional studio headphones

- Excellent sound quality and a rich bass reproduction
- Semi-open system, over-ear
- Padded ear cushions and headband, comfortable to wear
- 3 m cable with single-sided cable inlet
- 3.5 mm plug with 6.3 mm adapter

Model	HP-565
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	500 mW
Transmission range, headphones	20-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	104 dB/mW
Cable	3 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	350 g



MD-5000DR

Order No. 0220860

Stereo headphones, for applications with drums and in the studio.

- Perfectly closed system for suppressing ambient noise
- Good bass reproduction
- Extra secure fit
- Padded ear cushions
- 3 m helix cable with single-sided cable inlet
- Right-angle 3.5 mm plug, gold-plated, with thread for a secure connection to supplied 6.3 mm adapter

Model	MD-5000DR
Headphone driver	neodymium, Ø 40 mm
Type of transducer	dynamic
Max. input power	500 mW
Transmission range, headphones	10-20,000 Hz
Nominal impedance, headphones	32 Ω
Headphone sensitivity	105 dB/mW
Cable	3 m, single-sided cable inlet
Plug	3.5 mm plug, gold-plated
Adapter	6.3 mm plug, gold-plated
Weight w/o cable	365 g

