

### PAK-415

Order No. 0256050



#### Active power PA speaker system with 2-channel amplifier, 700 W

- Compact 15/2 full range system with robust plastic cabinet
- Modern amplifier system (bass: class D, tweeter: class A/B)
- Sound pressure at nominal power: 124 dB
- 4 selectable presets: normal, hi-fi, DJ and voice, switchable high-pass filter: 75 Hz
- MIC/LINE input, switchable

Model	PAK-415
Total output power	700 W
Power rating (RMS)	450 (350+100) W
Frequency range	40-20,000 Hz
Input signal	260 mV/10 kΩ (line), 2 mV/10 kΩ (mic)
SPL	98 dB/W/m
Power supply	~ 230 V/50 Hz/550 VA
Dimensions	455 x 740 x 390 mm
Weight	18.7 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR, par. out



### PAK-412

Order No. 0256040



#### Active power PA speaker system with 2-channel amplifier, 700 W

- Compact 12/2 full range system with robust plastic cabinet
- Modern amplifier system (bass: class D, tweeter: class A/B)
- Sound pressure at nominal power: 124 dB
- 4 selectable presets: normal, hi-fi, DJ and voice, switchable high-pass filter: 75 Hz
- Mic/line input, switchable

Model	PAK-412
Total output power	700 W
Power rating (RMS)	450 (350+100) W
Frequency range	40-20,000 Hz
Input signal	260 mV/10 kΩ (line), 2 mV/10 kΩ (mic)
SPL	98 dB/W/m
Power supply	~ 230 V/50 Hz/500 VA
Dimensions	405 x 670 x 340 mm
Weight	17.3 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR, par. out



### PAK-410

Order No. 0256030



#### Active power PA speaker system with 2-channel amplifier, 500 W

- Compact 10/2 full range system with robust plastic cabinet
- Modern amplifier system (bass: class D, tweeter: class A/B)
- Sound pressure at nominal power: 121 dB
- 4 selectable presets: normal, hi-fi, DJ and voice, switchable high-pass filter: 75 Hz
- Mic/line input, switchable

Model	PAK-410
Total output power	500 W
Power rating (RMS)	300 (250+50) W
Frequency range	55-20,000 Hz
Input signal	260 mV/10 kΩ (line), 2 mV/10 kΩ (mic)
SPL	97 dB/W/m
Power supply	~ 230 V/50 Hz/400 VA
Dimensions	340 x 560 x 290 mm
Weight	12 kg
Inputs	1 x comb. XLR/6.3 mm (line/mic)
Outputs	1 x XLR, par. out

