

Speakers

Horn Speakers

NR-60KS

Order No. 0163010



Weatherproof horn speaker, with high power capability.

- 16 Ω speaker system
- IP66 tested, protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust light grey plastic housing
- Aluminium mounting bracket

| Model | NR-60KS |
|-----------------------|-------------------|
| Total power rating | 60 W |
| Power rating (RMS) | 30 W |
| Frequency range | 340-10,000 Hz |
| SPL | 103 dB/W/m |
| Admiss. ambient temp. | -20 °C to +50 °C |
| Dimensions | Ø 146 mm x 160 mm |
| Weight | 2 kg |



NR-40KS

Order No. 0161370



Weatherproof horn speaker

- 16 Ω speaker system
- IP66 tested, protected against powerful water jets
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel

| Model | NR-40KS |
|-----------------------|--------------------|
| Total power rating | 60 W |
| Power rating (RMS) | 30 W |
| Frequency range | 180-7,000 Hz |
| SPL | 113 dB/W/m |
| Beam angle | H: 110°/V: 45° |
| Admiss. ambient temp. | -20 °C to +50 °C |
| Dimensions | 400 x 200 x 385 mm |
| Weight | 3 kg |



NR-35KS

Order No. 0160250



Horn speaker

- Moisture-proof
- 8 Ω speaker system

| Model | NR-35KS |
|-----------------------|--------------------|
| Total power rating | 40 W |
| Power rating (RMS) | 20 W |
| Frequency range | 300-12,000 Hz |
| SPL | 107 dB/W/m |
| Beam angle | H: 100°/V: 50° |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 280 x 170 x 215 mm |
| Weight | 1.4 kg |



NR-33KS

Order No. 0160650



Weatherproof horn speaker

- IP66 tested, protected against powerful water jets
- 8 Ω speaker system
- Suitable for general indoor and outdoor applications
- Robust plastic housing
- Mounting bracket and screws made of stainless steel

| Model | NR-33KS |
|-----------------------|--------------------|
| Total power rating | 25 W |
| Power rating (RMS) | 12 W |
| Frequency range | 275-7,000 Hz |
| SPL | 106 dB/W/m |
| Beam angle | H: 100°/V: 50° |
| Admiss. ambient temp. | -20 °C to +50 °C |
| Dimensions | 250 x 145 x 272 mm |
| Weight | 1.5 kg |

