

## TK-600

Order No. 0234890

### Dynamic vocal microphone

- Impressive vocal microphone, also meets high requirements, available at an attractive price
- Powerful and brilliant sound reproduction
- Minimised handling noise
- Low susceptibility to acoustic feedback
- Mechanical stability
- Low-noise reed switch resistant to wear
- Supplied with connection cable

Model	TK-600
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	147 dB
Housing material	diecast metal
Weight	380 g
Cable	XLR, bal.
Connection	XLR, bal.



## TK-350

Order No. 0234880

### Dynamic vocal microphone

- Frequency response optimised for vocals
- Clear voice reproduction
- Powerful band sound
- Minimised handling noise and structure-borne noise, low susceptibility to acoustic feedback
- High-quality reed switch allows silent switching actions
- Supplied with connection cable

Model	TK-350
Polar pattern	cardioid
System	dynamic
Audio frequency range	80-12,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	145 dB
Housing material	diecast metal
Weight	380 g
Cable	XLR, bal., XLR, bal.
Connection	XLR, bal.



## TM-929

Order No. 0234940

### Dynamic vocal microphone

- High-quality entry-level microphone, classic design
- Robust body
- Suppression of handling noise and acoustic feedback
- Low-noise reed switch
- Supplied with connection cable

Model	TM-929
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-15,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	148 dB
Housing material	diecast metal
Weight	350 g
Cable	XLR, bal., 6.3 mm plug, unbal.
Connection	XLR, bal.

