

### UF-20R/5

Order No. 0257210



#### 2-channel true diversity UHF PLL wideband receiver

- Bandwidth: 75 MHz
- 15 groups, each with 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- RF output and mains voltage output for easily cascading up to 10 x UF-20R/5 receiver without additional splitter
- REMOSET technology for receiver/transmitter synchronisation
- Auto-scan function
- Pilot tone and noise squelch
- Equalizer function
- LED for indicating RF level and AF level

- Backlit display for indicating battery status of the transmitter, frequency setup, active antenna
- Metal housing
- Power supply for optional antenna booster UB-900I directly via antenna inputs

**There are restrictions or requirements within the EU. Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



Model	UF-20R/5
Description	wireless receiver
Carrier frequency range	530-605 MHz
Audio frequency range	50-18,000 Hz
THD	< 0.5%
Dynamic range	> 108 dB
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	~ 100-240 V/50-60 Hz/25 VA
Dimensions receiver	480 x 44 x 214 mm
Weight receiver	2.9 kg

### UF-20S/5

Order No. 0257220

#### Single-channel true diversity UHF PLL wideband receiver

- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Auto-scan function
- Pilot tone and noise squelch
- Equalizer function
- LED for indicating RF level and AF level
- Backlit display for indicating battery status of the transmitter, frequency setup, active antenna
- Metal housing

- Power supply for optional antenna booster UB-900I directly via antenna inputs

**There are restrictions or requirements within the EU. Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



Model	UF-20S/5
Description	wireless receiver
Carrier frequency range	530-605 MHz
Audio frequency range	50-18,000 Hz
THD	< 0.5%
Dynamic range	> 108 dB
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	212 x 44 x 214 mm
Weight receiver	1.4 kg

### JSS-20/5

Order No. 0257200

#### Dynamic hand-held UHF PLL transmitter

- Dynamic microphone cartridge (cardioid polar pattern) with minimised feedback susceptibility as well as suppression of handling noise/structure-borne noise
- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-15 dB to +15 dB)

- Lock function/mute function
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power
- Supplied with robust transport case, stand clamp and 8 ID caps

**There are restrictions or requirements within the EU. Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

Model	JSS-20/5
Polar pattern	cardioid
System	dynamic
Carrier frequency range	530-605 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	> 20 h
Dimensions	Ø 50 mm x 260 mm
Weight	340 g

