

GM-5212LDU

Order No. 0236290




GM-5215LDU

Order No. 0236310



Double gooseneck microphones with LED

- Back electret supercardioid cartridges
- High sensitivity
- 10 dB attenuator
- Low cut switch
- LED for indicating operating status
- Flexible positioning due to vertically adjustable goosenecks (160°)
- Common 3-pole XLR plug
- Operation via +48 V phantom power



Model	GM-5212LDU	GM-5215LDU
Polar pattern	supercardioid	supercardioid
System	back electret	back electret
Audio frequency range	80-18,000 Hz	80-18,000 Hz
Nominal impedance	220 Ω	220 Ω
Sensitivity	16 mV/Pa	16 mV/Pa
Max. sound pressure	125 dB	125 dB
Power supply	= 48 V phantom power	= 48 V phantom power
Dimensions	415 mm	492 mm
Weight	315 g	335 g
Connection	XLR, bal.	XLR, bal.

GM-5212L

Order No. 0234410




GM-5218L

Order No. 0234420



Electret gooseneck microphones with LED

- Supercardioid polar pattern
- Natural sound
- Frequency response perfectly matched to the voice, precise voice reproduction
- Low susceptibility to acoustic feedback
- LED for indicating operating status
- Solid and high-quality workmanship to ensure a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power or desktop base DMS-5



Model	GM-5212L	GM-5218L
Polar pattern	supercardioid	supercardioid
System	electret	electret
Audio frequency range	80-18,000 Hz	80-18,000 Hz
Nominal impedance	220 Ω ± 30%	220 Ω
Sensitivity	12.6 mV/Pa	12.6 mV/Pa
Max. sound pressure	125 dB	125 dB
Power supply	= 48 V phantom power	= 48 V phantom power
Dimensions	465 mm	615 mm
Weight	165 g	185 g
Connection	XLR, bal.	XLR, bal.

GML-5212

Order No. 0234560



GML-5218

Order No. 0234570



Electret gooseneck microphones with LED

- 3 replaceable microphone cartridges with different polar patterns (cardioid, supercardioid and omnidirectional)
- Excellent speech intelligibility
- -10 dB PAD switch
- Switchable low cut filter
- LED for indicating operating status
- Solid and high-quality workmansh. to ensure a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power or mic. base DMS-5



Model	GML-5212	GML-5218
Polar pattern	cardioid/supercardioid/omnidir.	cardioid/supercardioid/omnidir.
System	back electret	back electret
Audio frequency range	80-18,000 Hz	80-18,000 Hz
Nominal impedance	220 Ω ± 30%	220 Ω ± 30%
Sensitivity	16 mV/Pa	16 mV/Pa
Max. sound pressure	125 dB	125 dB
Power supply	= 48 V phantom power	= 48 V phantom power
Dimensions	465 mm	615 mm
Weight	230 g	245 g
Connection	XLR, bal.	XLR, bal.

GM-5212

Order No. 0234380




GM-5218

Order No. 0234390



Electret gooseneck microphones

- Supercardioid polar pattern
- Excellent sound with a very high speech intelligibility
- Minimum susceptibility to acoustic feedback
- Solid and high-quality workmanship to ensure a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power or microphone base DMS-5



Model	GM-5212	GM-5218
Polar pattern	supercardioid	supercardioid
System	back electret	back electret
Audio frequency range	80-18,000 Hz	80-18,000 Hz
Nominal impedance	220 Ω ± 30%	220 Ω
Sensitivity	16 mV/Pa	16 mV/Pa
Max. sound pressure	125 dB	125 dB
Power supply	= 48 V phantom power	= 48 V phantom power
Dimensions	455 mm	605 mm
Weight	165 g	185 g
Connection	XLR, bal.	XLR, bal.